

**DAO PHAY NGÓN CARBIDE 3 ME PHAY TINH
TUNGSTEN CARBIDE 3 FLUTES END MILLS**


RIGHT-HAND ROTATION / LEFT-HAND ROTATION - UP CUT



Type 1



Type 2



LOWER FINISHING


RIGHT-HAND ROTATION / LEFT-HAND ROTATION - DOWN CUT



Type 3



Type 4



UPPER FINISHING

**3 flute spiral router. For CNC machines and for portable routers. For wood, plastic material.
Feed rate 2 – 16 m/min of 18000 - 24000 RPM. Finishing operation.**

CODE Type 1	CODE Type 2	CODE Type 3	CODE Type 4	Cut diameter ĐK chuỗi cắt	Flute length Chiều dài cắt l	Total length Tổng chiều dài L	Shank diameter ĐK chuỗi D
121-3060-20	122-306-20	123-306-20	124-306-20	6	20	60	6
121-3060-30	122-3060-30	123-3060-30	124-3060-30	6	30	70	6
121-3080-22	122-3080-22	123-3080-22	124-3080-22	8	22	70	8
121-3080-32	122-3080-32	123-3080-32	124-3080-32	8	32	80	8
121-3100-32	122-3100-32	123-3100-32	124-3100-32	10	32	80	10
121-3100-42	122-3100-42	123-3100-42	124-3100-42	10	42	90	10
121-3100-52	122-3100-52	123-3100-52	124-3100-52	10	52	100	10
121-3120-32	122-3120-32	123-3120-32	124-3120-32	12	32	80	12
121-3120-42	122-3120-42	123-3120-42	124-3120-42	12	42	90	12
121-3120-52	122-3120-52	123-3120-52	124-3120-52	12	52	100	12
121-3140-42	122-3140-42	123-3140-42	124-3140-42	14	42	90	14
121-3140-52	122-3140-52	123-3140-52	124-3140-52	14	52	100	14
121-3160-32	122-3160-32	123-3160-32	124-3160-32	16	32	80	16
121-3160-42	122-3160-42	123-3160-42	124-3160-42	16	42	90	16
121-3160-52	122-3160-52	123-3160-52	124-3160-52	16	52	100	16
121-3160-62	122-3160-62	123-3160-62	124-3160-62	16	62	110	16
121-3180-52	122-3180-52	123-3180-52	124-3180-52	18	52	100	18
121-3180-75	122-3180-75	123-3180-75	124-3180-75	18	72	120	18
121-3200-52	122-3200-52	123-3200-52	124-3200-52	20	52	100	20
121-3200-102	122-3200-102	123-3200-102	124-3200-102	20	102	150	20